

Fire Sprinkler Checklist



One and Two Family Dwellings

All REFERENCES are to the 2007 NFPA standard 13D as amended by City of Scottsdale interpretations and applications. An asterisk* indicates a local amendment.		NOT SHOWN	INCORRECT	COMPLETED
1.	Provide 3 sets of floor plan to scale, signed by min. NICET III. 4.6*, 9-2(General).			
2.	Provide system shutoff valves per 7.1, 7.2, 7.3, 8.1.3*.			
3.	Provide sprinklers in all locations as required by 7.5* and 8.6.*			
4.	Comply with sprinkler manufacturer design requirements or demonstrate compliance with spacing and hydraulic calculations per 8.1.1.			
5.	Network systems shall be designed per 8.4.3.3.3*.			
6.	Hydraulic calculations shall comply with 6.5*, 7.5*, and 8.4.4.			
7.	Provide minimum density of .05 gpm for required number of design sprinklers per 8.1.1.2.2, 8.1.2 for new detached construction.			
8.	Provide proper temperature rated heads per 7.5.5*.			
9.	Show location and orifice size of system drain and test connection per 7.2*.			
10.	Check water meter friction loss per table 8.4.4(G) or mfgr data sheet.			
11.	Provide water supply complying with 6.1.2*, 6.2, and 6.5*.			
12.	Provide alarms per 7.6*.			
13.	Unsupervised pipe limitations per 7.8*.			
14.	Pump installations per 6.2*.			
15.	Heads installed outside of listing shall comply with policy letter dated 7/01/06.			
16.	Provide heads for mechanical units and barbeques per COS policy.			
17.	Check pressure for every lot to account for pressure zones differentials per COS Policy.			
18.	Position sprinklers for sloped ceilings per 8.1.3.1.3.			
19.	Position sprinklers from obstructions per 8.2.5.			
Planning & Development Services Department				

7447 E Indian School Rd. Ste 125, Scottsdale, AZ 85251 • Phone: 480-312-7080 • Fax: 480-312-7781